



2931 Exon Ave. ■ Cincinnati, Ohio 45241
(513) 733-0883 ■ FAX (513) 733-1096

CLOSED CELL VITON SPONGE (S-2-S)

COLOR:	BLACK		
COMPOUND:	VITON		
THICKNESS:	1/8", 1/4", 3/8", 1/2"		
SHEET SIZE:	24" x 24" AND 24" x 48"		
DENSITY:	10-25 PCF		
CONDITIONING:	SOFT		
25% COMPRESSION DEFLECTION:	3-7 PSI		
25% COMPRESSION DEFLECTION: (7 DAYS @ 400°F):	5-9 PSI		
COMPRESSION SET: (22 HRS @ 75°F):	17-27%		
LOW TEMPERATURE:	-45°F		
HIGH TEMPERATURE:	450°F		
WATER ABSORPTION:	6% MAX		
TEAR RESISTANCE:	GOOD		
RESISTANCE:			
ACID:	EXCELLENT	KETONES:	EXCELLENT
ALKALI:	EXCELLENT	CHLORINATED SOLVENTS:	EXCELLENT
GASOLINE AND OIL:	EXCELLENT	OXIDATION:	EXCELLENT
AROMATIC HYDROCARBONS:	EXCELLENT	OZONE:	EXCELLENT

*VITON SPONGE WILL NOT PROPAGATE FLAME.

This information is furnished as a guide for selecting materials. NRC disclaims liability for results or use of this information. It is the customer's responsibility to obtain and test samples when determining suitability of material for a particular application.